

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
12 May 2005 (12.05.2005)

PCT

(10) International Publication Number  
**WO 2005/043003 A1**

(51) International Patent Classification<sup>7</sup>: **F16G 1/12,**  
D07B 1/06

(21) International Application Number:  
PCT/EP2004/052557

(22) International Filing Date: 15 October 2004 (15.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
03104053.8 3 November 2003 (03.11.2003) EP

(71) Applicant (for all designated States except US): NV  
Bekaert SA [BE/BE]; Bekaertstraat 2, B-8550 ZW-  
EVEGEM (BE).

(72) Inventors; and


(75) Inventors/Applicants (for US only): VANCOMPER-  
NOLLE, Stijn [BE/BE]; Franklin Rooseveltlaan 173,  
B-9000 GENT (BE). BRUYNEEL, Paul [BE/BE];  
Wielsbeeksestraat 119, B-8710 WIELSBEKE (BE).  
VANDERBEKEN, Bert [BE/BE]; Langveld 10, B-8790  
WAREGEM (BE).

(74) Agent: SEYNHAEVE, Geert; Bekaertstraat 2, B-8550  
ZWEVEGEM (BE).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,

[Continued on next page]

(54) Title: FINE STEEL CORD WITH A LOW STRUCTURAL ELONGATION



(57) Abstract: A fine steel cord for the reinforcement of syn-  
chronous belts is presented. The fine cord has a distinct load  
elongation curve characterized by a very low structural elonga-  
tion (below 0.09% preferably below 0.06%), and a high equiva-  
lent modulus between 0.2 and 20% of the breaking ' load. The  
favorable results are maintained when the cords are coated with  
an elastomer coating. Such a fine steel cord reduces the geomet-  
rical spread on the tooth pitch of the synchronous belts during  
use. A method to produce such a fine steel cord is also presented.



TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— *with international search report*

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*